

**CLAIM LISTING**

1. (Original): A method comprising validating a configuration setting of a first application for use with a second application, wherein:

the configuration setting including a first field and a first description of a first condition for the first field;

the second application is composed of computer instructions, the computer instructions having an attribute, the attribute providing a second description of a second condition for a second field; and

the validating includes:

if the first field corresponds to the second field, then comparing the first description of the first condition with the second description of the second condition to determine whether the first condition is met by the second condition; and

if met, then determining that the configuration setting is valid for use with the second application.

2. (Previously presented): A method as described in claim 1, wherein the first and second conditions are value constraints selected from the group consisting of:

an integer range;

a float range;

1                   a value set;  
2                   a string pattern;  
3                   cardinality of a collection;  
4                   a mandatory value; and  
5                   an optional value.

6  
7                   3. (Original): A method as described in claim 1, wherein the first and  
8                   second conditions are default values.

9  
10                  4. (Original): A method as described in claim 1, wherein the first and  
11                  second conditions are textual descriptions selected from the group consisting of:

12                  a description of units in which the respective first and second fields are  
13                  expressed;  
14  
15                  a description of meanings of the respective first and second fields; and  
16  
17                  an example of values of the first and second fields.

18  
19                  5. (Original): A method as described in claim 1, wherein the attribute:  
20                  is a declarative tag that may be retrieved from and during execution of  
21                  the second application; and  
22  
23                  does not determine the value of the field.

24  
25                  6. (Original): A method as described in claim 1, further comprising

communicating a result of the validating to the first application.

7. (Original): A method as described in claim 1, wherein the configuration setting further comprises a field type.

8. (Original): One or more computer-readable media comprising computer-executable instructions that, when executed, perform the method as recited in claim 1.

9. (Original): A method comprising:

reading a first configuration setting of a first application including a first field and a first description of a first condition for the first field;

examining a second application to find a second configuration setting that corresponds to the first configuration setting, wherein the second application is composed of computer instructions, the computer instructions having an attribute, the attribute providing a second description of a second condition for a second field, the second configuration setting having the second field and the second description; and

comparing the second description of the second condition with the first description of the first condition to determine whether the second condition is met by the first condition, and if met then determining that the second configuration setting is valid for use with the first application.

1  
2       10. (Previously presented): A method as described in claim 9, wherein  
3 the first and second conditions are value constraints selected from the group  
4 consisting of:

- 5           an integer range;  
6           a float range;  
7           a value set;  
8           a string pattern;  
9           cardinality of a collection;  
10          a mandatory value; and  
11          an optional value.

12  
13  
14       11. (Original): A method as described in claim 9, wherein the first and  
15 second conditions are default values.

16  
17  
18       12. (Original): A method as described in claim 9, wherein the first and  
19 second conditions are textual descriptions selected from the group consisting of:

- 20           a description of units in which the respective first and second fields are  
21 expressed;  
22           a description of meanings of the respective first and second fields; and  
23           an example of values of the first and second fields.

13. (Original): One or more computer-readable media comprising computer-executable instructions that, when executed, perform the method as recited in claim 9.

14. (Previously presented): A method comprising:  
executing a documenter to find a plurality of fields in an application,  
wherein:

the application is composed of computer instructions;

the computer instructions having attributes; and

each said attribute providing a description of a condition for a  
tive said field,

forming a configuration file having a plurality of configuration settings of the application, wherein each said configuration setting includes one said field and the description of the condition for the one said field;

outputting the configuration file; and

utilizing the configuration file to validate configuration settings.

15. (Previously presented): A method as described in claim 14, wherein the condition is a value constraint selected from the group consisting of:

an integer range;

a float range;

a value set;

1                   a string pattern;  
2                   cardinality of a collection;  
3                   a mandatory value; and  
4                   an optional value.

5  
6       16. (Original): A method as described in claim 14, wherein the  
7       condition is a default value.

8  
9  
10      17. (Original): A method as described in claim 14, wherein the  
11       condition is a textual description selected from the group consisting of:  
12                   a description of a unit in which the respective said field is expressed;  
13                   a description of meanings of the respective said field; and  
14                   an example of a value of the respective said field.

15  
16  
17      18. (Original): One or more computer-readable media comprising  
18       computer-executable instructions that perform the method as recited in claim 14.

19  
20      19. (Original): A method comprising:  
21                   generating a configuration file having a plurality of configuration settings  
22       derived from a first application, wherein:  
23                   the application is composed of computer instructions;  
24                   the computer instructions having attributes;

each said attribute providing a description of a condition for a field;

and

each said configuration setting having one said field and a corresponding said description; and

validating whether the first application is valid for use with a second said application by comparing each said configuration setting of the first application with a corresponding said configuration setting of the second said application to determine whether each said condition of the first application is met by a corresponding said condition of the second application.

20. (Previously presented): A method as described in claim 19, wherein each condition is a value constraint selected from the group consisting of:

an integer range;

a float range;

a value set;

a string pattern;

cardinality of a collection:

a mandatory value; and

an optional value.

21. (Original): A method as described in claim 19, wherein each condition is a default value.

1  
2 22. (Original): A method as described in claim 19, wherein each  
3 condition is a textual description selected from the group consisting of:

4 a unit in which a corresponding said field is expressed;

5 description of a meanings of a corresponding said field; and

6 an example of a value a corresponding said field.

7  
8 23. (Original): One or more computer-readable media comprising  
9 computer-executable instructions that, when executed, perform the method as  
10 recited in claim 19.

11  
12 24. (Original): A computer-readable medium comprising computer-  
13 executable instructions that, when executed by a computer, direct the computer to:

14 read a first configuration setting of a first application that includes a first  
15 field and a first description of a first condition for the first field; and

16 validate whether the first condition is met by a second application, wherein:

17 the second application is composed of computer instructions;

18 the computer instructions have an attribute that provides a second  
19 description of a second condition for a second field; and

20 the first condition is validated through comparison with the second  
21 condition.

1        25. (Previously presented): A computer-readable medium as described  
2        in claim 24, wherein the first and second conditions are value constraints selected  
3        from the group consisting of:

- 4            an integer range;  
5            a float range;  
6            a value set;  
7            a string pattern;  
8            cardinality of a collection;  
9            a mandatory value; and  
10          an optional value.

12  
13        26. (Original): A computer-readable medium as described in claim 24,  
14        wherein the first and second conditions are default values.

16  
17        27. (Original): A computer-readable medium as described in claim 24,  
18        wherein the first and second conditions are textual descriptions selected from the  
19        group consisting of:

- 20            a description of units in which the first and second fields are expressed;  
21            a description of meanings of the first and second fields; and  
22            an example of values of the first and second fields.

24  
25        28. (Original): A computer comprising:

1           a processor; and

2           memory configured to maintain:

3               a first application composed of computer instructions, the computer  
4           instructions having an attribute, the attribute providing a first description of  
5           a first condition for a first field;

6               a configuration file including a configuration setting of a second  
7           application having a second field and a second description of a second  
8           condition for the second field; and

9               a configuration module that, when executed on the processor,  
10           validates the configuration setting for use with the first application by  
11           comparing the second description of the second condition with the first  
12           description of the first condition to determine whether the second condition  
13           is met by the first condition, and if met, then determining that the  
14           configuration setting is valid for use with the first application.

17  
18       29. (Original): A computer as described in claim 28, wherein the second  
19           application is stored in the memory.

20  
21       30. (Original): A computer as described in claim 28, wherein the  
22           configuration file is received in a transmission from a network for storage in the  
23           memory.

1       31. (Original): A computer as described in claim 28, wherein the first  
2 and second conditions are selected from the group consisting of:

3           a value constraint;

4           a default value;

5           a description of units in which the first and second fields are expressed;

6           a description of meanings of the first and second fields; and

7           an example of values of the first and second fields.

9  
10       32. (Original): A computer comprising:

11           a processor; and

12           memory configured to maintain:

13                a first application composed of computer instructions, the computer  
14                instructions having an attribute, the attribute providing a first description of  
15                a first condition for a first field, and wherein a first configuration setting  
16                includes the first description and the first field;

17                a configuration file including a second configuration setting of a  
18                second application having a second field and a second description of a  
19                second condition for the second field; and

20                a configuration module that, when executed on the processor,  
21                validates the first configuration setting for use with the second application  
22                by comparing the first description of the first condition with the second  
23                description of the second condition to determine whether the first condition

is met by the second condition, and if met, then determining that the first configuration setting is valid for use with the second application.

33. (Original): A computer as described in claim 32, wherein the second application is stored in the memory.

34. (Original): A computer as described in claim 32, wherein the configuration file is received over a network and stored in the memory.

35. (Original): A computer as described in claim 32, wherein the first and second conditions are selected from the group consisting of:

a value constraint;

a default value:

a description of units in which the first and second fields are expressed;

a description of meanings of the first and second fields; and

an example of values of the first and second fields.

36. (Previously presented): A content server comprising:

a broadcast transmitter configured to provide media content to a client in response to a request from the client;

a processor; and

memory configured to maintain:

1                   a first application that when executed provides media content for  
2 broadcast by the broadcast transmitter, wherein the application is composed  
3 of computer instructions, the computer instructions have attributes, and  
4 each said attribute provides a description of a condition for a field; and

5                   a documenter that is executable on the processor to generate a  
6 configuration file having a configuration setting of the first application,  
7 wherein the configuration setting includes the field and the description of  
8 the condition for the field.

10

11                37. (Previously presented): A content server as described in claim 36,  
12 wherein the condition is a value constraint selected from the group consisting of:  
13                an integer range;  
14                a float range;  
15                a value set;  
16                a string pattern;  
17                cardinality of a collection;  
18                a mandatory value; and  
19                an optional value.

21

22                38. (Previously presented): A content server as described in claim 36,  
23 wherein the condition is a default value.

1           39. (Previously presented): A content server as described in claim 36,  
2           wherein the condition is a textual descriptions selected from the group consisting  
3           of:

- 4           a description of units in which the first and second fields are expressed;  
5           a description of meanings of the first and second fields; and  
6           an example of values of the first and second fields.

7

8           40. (Original): A content server comprising:

9           a first application composed of computer instructions, the computer  
10          instructions having attributes, and each said attribute providing a description of a  
11          condition for a field;

12          a configuration module that is executable to validate whether each said  
13          condition is met by a second application; and

14          a documenter that is executable to generate a configuration file having a  
15          configuration setting of the first application, wherein the configuration setting  
16          includes the field and the description of the condition.

17

18           41. (Original): A content server as described in claim 40, further  
19          comprising a broadcast transmitter, wherein the first application, when executed,  
20          provides content for broadcast by the broadcast transmitter.

21

22           42. (Previously presented): A content server as described in claim 40,

1 wherein each said condition is a value constraint selected from the group  
2 consisting of:

- 3 an integer range;  
4 a float range;  
5 a value set;  
6 a string pattern;  
7 cardinality of a collection;  
8 a mandatory value; and  
9 an optional value.

11  
12 43. (Original): A content server as described in claim 40, wherein each  
13 said condition is a default value.

14  
15 44. (Original): A content server as described in claim 40, wherein each  
16 said condition is a textual description selected from the group consisting of:  
17  
18 a description of a unit in which a respective said field is expressed;  
19 a description of a meaning of a respective said field; and  
20 an example of a values of a respective said field.

21  
22 45. (Original): A system comprising:  
23  
24 a network;  
25 a first computer communicatively coupled to the network and including a

1       first application composed of computer instructions, the computer instructions  
2       having a first attribute that provides a first description of a first condition for the  
3       first field, wherein a first configuration setting includes the first field and the first  
4       description;

5               a second computer communicatively coupled to the network and including:

6                       a second application composed of computer instructions having a  
7       second attribute that provides a second description of a second condition  
8       for a second field; and

9                       a configuration module that is executable by the second computer to  
10      validate the first configuration setting for use with the second application  
11      by comparing the first description of the first condition with the second  
12      description of the second condition.

13  
14  
15       46. (Original): A system as described in claim 45, wherein the first  
16      computer is configured as a set-top box and the second computer is configured as  
17      a content server.

18  
19  
20       47. (Original): A system as described in claim 45, wherein the first and  
21      second conditions are selected from the group consisting of:

22               a value constraint;

23               a default value;

24  
25               a description of units in which the first and second fields are expressed;

1 a description of meanings of the first and second fields; and  
2 an example of values of the first and second fields.

3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25